

Modifry's Suction Cup Camera Mount

This product is a generic suction cup camera mount that can be used on any flat, smooth, non-porous surface such as glass, smooth plastic, or painted metal/fiberglass. Do not use this mount on flexible surfaces, bare fiberglass, automobile dashboards, surfaces painted with a flat (primer) paint, or surfaces that have any texture at all. When mounted on these types of surfaces the mount may at first seem to hold tightly, but as air slowly seeps in through surface irregularities the mount will lose its holding power and will eventually fall off. If in doubt, test the surface by attaching the mount and waiting at least 8 hours (overnight). If the mount is not as secure as when it was first installed DO NOT USE IT.

This mount is rated for cameras weighing 2 pounds or less. DO NOT OVERLOAD.

Caution - Camera mounts that are improperly attached or overloaded can come loose and cause property damage or personal injury. Modifry Products cannot control installation or mounting methods and is not responsible for loss of equipment, property damage, or injury caused by use of these products. Use of camera mounts is at your own risk!

Installation and use: See photos on next page

1. Clean and dry the mounting surface to remove all traces of dirt or foreign matter. If mounting to glass or plastic surfaces that have been cleaned with a solution containing silicone or silicon-like products you must clean the surface with solvent to remove the silicone. (some cleaning solutions have these additives to make glass 'sparkle' and reduce the ability of dirt to cling to the glass)
2. DO NOT WET OR MOISTEN THE SURFACE OR THE SUCTION CUP. This product must be used dry.
3. Make sure the locking lever is in the down position, then position the suction cup against the surface and firmly depress the "PUSH" button.
4. While holding the PUSH button, lift the locking lever to the full upright position.
5. Turn the locking ring all the way down, tight against the swivel head.
6. Rotate the head of the mount (or your camera) to thread the ¼-20 bolt into the bottom of your camera as far as it will easily go. For maximum holding power you want to thread use as much of the bolt as possible into the base of the camera, but do not exert enough force to damage the camera base.
7. Firmly snug up the locking ring against the base of the camera. This is very important, as a loose locking ring can allow the camera to vibrate and unscrew itself off the swivel head.
8. Loosen the thumb screw on the side of the arm just enough to allow the head to rotate and swivel, then aim the camera and tighten the thumb screw.
9. Give the camera and mount a firm shake to make sure nothing is loose.

To remove the mount, flip the locking lever down, depress the PUSH button, and lift the edge of the suction cup.

Hints:

- It some cases it's easier to attach your camera to the mount before attaching the suction cup to the surface.
- Once the camera is aimed you can remove the entire mount/camera for safe-keeping and replace it later without having to re-aim the swivel head.
- If you use the 'upside-down' mounting position make sure your camera will invert the recorded image. Some do, some don't. Do not be fooled if you see the image in the camera display screen 'right side up'. This will occur on all cameras, even those that do not automatically invert the recorded image. It's best to take a short video, remove the camera, and playback the video to be sure it records properly.
- If you have a larger camera and are having trouble getting 'just the right mounting angle' you may want to consider these options:
 - Mount the camera on the side (passenger) window
 - Mount the camera to the inside of the rear window (sedans only – not for convertible tops even if the rear window is glass as the mount will shake and possibly come loose)
 - Purchase our 'swivel head extension'. It adds an extra 1-2" of length to the mounting arm and provides nearly unlimited angle adjustments. See web site for details.

This product is guaranteed against defects in materials or workmanship for a period of one year from date of purchase. If you experience any trouble with this camera mount please contact us (see below) for help and before returning any items. If you've lost a piece of the mount or require spare parts please contact us for information. Do not return products without prior authorization – credit will NOT be issued. All items are subject to a re-stocking charge of 20%.

Web site for more information: www.modify.com Email for questions of any kind: bob@modify.com

Photo 1 – Camera Mount parts



Photo 2 – Press button firmly to release air



Photo 3 – Lift locking lever to secure the mount



Photo 4 – Install your camera – tighten lock ring against bottom of camera to be sure camera doesn't come loose.



Photo 5 – Remove by pressing button and lifting tab on edge of suction cup to release vacuum.



Photo 6 – Upside down mounting on windshield – only if your camera can operate in this orientation.

